



PROVIDE 2" CONDUIT (FULL WIDTH OF APRON) WHEN REQUIRED BY VILLAGE STAFF

**MATERIALS:**

- CONCRETE: 6" MINIMUM THICKNESS ON 4" COMPACTED AGGREGATE (CA-6) BASE COURSE (8" FOR COMMERCIAL)
- ASPHALT: 2" HMA SURFACE COURSE TO BE INSTALLED ON 8" COMPACTED AGGREGATE (CA-6) BASE COURSE
- PAVERS: PAVERS TO BE INSTALLED ON MINIMUM 8" AGGREGATE BASE COURSE AND MINIMUM 1" SAND SETTING BED (OR AS REQUIRED BY MANUFACTURER'S SPECIFICATIONS)

**NOTES:**

1. IF CURB AND/OR SIDEWALK ARE TO BE REPLACED, THEY SHALL BE POURED PRIOR TO THE DRIVEWAY APRON AND SHALL BE CURED PRIOR TO APRON WORK BEGINNING.
2. IF ANY CURB IS TO BE REPLACED, THE ADJACENT ASPHALT PAVEMENT SHALL BE REPLACED IN ACCORDANCE WITH THE "CURB REPLACEMENT DETAIL".
3. ANY TIME A VALVE BOX, BUFFALO BOX, OR OTHER AT-GRADE INFRASTRUCTURE IS LOCATED WITHIN THE DRIVEWAY APRON, A MINIMUM 12"x12" SQUARE SHALL BE FORMED AROUND THE UTILITY USING FULL-DEPTH EXPANSION JOINT MATERIAL. IF 12"x12" IS INSUFFICIENT, THE SIZE OF THE SQUARE SHALL BE INCREASED SO THE UTILITY IS SURROUNDED BY NO LESS THAN 2" OF CONCRETE ON ALL SIDES.
4. ANY CURB REQUIRING MODIFICATION (BARRIER TO DEPRESSED, OR VICE VERSA) SHALL BE COMPLETELY REMOVED AND REPLACED. SAW-CUTTING EXISTING CURB SHALL NOT BE PERMITTED UNLESS IT IS DONE TO ACCOMMODATE REPLACEMENT.

**REVISION: 8/6/20**



VILLAGE OF RIVER FOREST  
PUBLIC WORKS - ENGINEERING  
400 PARK AVE.  
RIVER FOREST, IL 60305  
PH. (708)-366-8500

**DRIVEWAY APRON DETAIL**